

CAST BALL VALVE CF3M

STAINLESS STEEL



Tel: 03-5569 2933 (6 Lines)
Fax: 03-5569 2588, 5569 2788
Email: mercoid@mercoid.com.my,
valmicro@valmicro.com.my
http://www.mercoid.com.my

DESIGN FEATURE

- Tube bore
- 1/2" - 4" (DN15 - DN100)
- Design as per ANSI B16.34 / BPE
- Blow-Out-Proof stem design
- ISO 5211 direct mounting flange
- End connection :
Tri-Clamp, BPE / ISO /
DIN Ext. tube end
- Option : Cavity filled seat,
Extended stem, Purge port,
Anti-static device



Body	ASTM A351 Gr.CF3M
Ball / Stem	ASTM A351 Gr.CF3M / SS316L
Seat	TFM1600
Working Pressure	1/2" - 2" 1000 PSI (PN63) 2-1/2" - 4" 720 PSI (PN40)
Temperature Range	-40 to 356°F (-40 to 180°C)

DESIGN FEATURE

- Tube bore
- 1/2" - 4" (DN15 - DN100)
- Blow-Out-Proof stem design
- End connection :
Tri-Clamp, 3A tube end,
DIN 11850 tube end



Option : Cavity filled seat



Option : Locking device, Cavity filled seat



Option : Cavity filled seat

Body	ASTM A351 Gr.CF8M
Ball / Stem	CF8M / SS316
Seat	TFM1600
Working Pressure	1/2" - 2" 1000 PSI (PN63) 2-1/2" - 4" 800 PSI (PN40)
Temperature Range	-4 to 356°F (-20 to 180°C)

CASTING BALL VALVE SUPER ALLOY



PNEUMATIC ACTUATED VALVE



AVAILABLE RANGE

Screwed ball valve	1/4" - 8"
Flanged ball valve	1/2" - 12"
Multi-way ball valve	1/2" - 8"
Butterfly valve	11/2" - 24"

Limit Switch Box	Weather proof Explosion proof Special material housibg
Air Filter	AFC Series BFC Series
Positioner	PPL / PPP Pneumatic-Pneumatic EPL / EER Electro-Pneumatic
Solenoid Valve	5/2 Way for spring return 3/2 Way for double acting
Actuator	Double acting Spring return

ELECTRIC ACTUATED VALVE



AVAILABLE RANGE

Screwed ball valve	1/4" - 4"
Flanged ball valve	1/2" - 12"
Multi-way ball valve	1/2" - 8"
Butterfly valve	1-1/2" - 24"

*Specification given are subject to changed without further notice.