


Tel: 03-5569 2933 (6 Lines) Fax: 03-5569 2588, 5569 2788 Email: mercoid@mercoid.com.my, valmicro@valmicro.com.my http://www.mercoid.com.my


STEAM TRAPTHERMODYNAMIC TYPE


CAST IRON / FORGED STEEL / STAINLESS STEEL















APPLICATION

Suitable for steam (Refer to corrosion resistance table for valve materials selection).

SPECIFICATION

Size Range Body Material Pressure Rating Working Temperature Connection 1/4" to 2" Cast Iron, Ductile Iron, Forged steel, Stainless Steel Up to 45 Bar Up to 425°C

Threaded, Socket weld, Flanged end

MATERIAL

	Parts	Material	
1	Cover	Cadmium Coated St.37	
2	Cover Gasket	Stainless Steel AISI 304	
3	Disc	Stainless Steel AISI 420	
4	Seat	Stainless Steel AISI 420	
5	Seat Gasket	Stainless Steel AISI 304	
6	Body	Cast Iron / Forged Steel - A105N / Stainless Steel - F316	
7	Strainer Screen	Stainless Steel AISI 304	
8	Discharge Bolt	Stainless Steel AISI 304	

DIMENSIONSUnit: mm

Cizo (DNI)	Flanged	Threaded	Н		
Size (DN)	L	L1			
15	150	95	60		
20	150	95	60		
25	160	95	60		
32	205	170	115		
40	205	170	115		
50	240	200	120		