

SOLENOID VALVE



Tel: 03-5569 2933 (6 Lines) Fax: 03-5569 2588, 5569 2788
Email: mercoid@mercoid.com.my, valmicro@valmicro.com.my
<http://www.mercoid.com.my>

MINIATURE & HIGH PRESSURE SOLENOID VALVE



2/2 WAY MINIATURE - DIRECT ACTING AND HIGH PRESSURE SOLENOID VALVE

Normally Closed or Normally Open Type
Connection Thread 1/8" - 1/2"
Body Material Brass, Stainless Steel, Plastic
Working Pressure 0 - 170 Bar

GENERAL SOLENOID VALVE



2/2 WAY ZERO DIFFERENTIAL PRESSURE - DIRECT ACTING SOLENOID VALVE

WITH WIRE TYPE / DIN TYPE

Normally Closed Type or Normally Open Type
Connection Thread 1/8" - 2"
Flanged 1" - 8"
Body Material Brass, Cast Iron, Stainless Steel
Working Pressure 0 - 10 Bar

HIGH TEMPERATURE STEAM SOLENOID VALVE



2/2 WAY - PISTON SOLENOID VALVE FOR HOT WATER , STEAM

Normally Closed or Normally Open Type
Connection Thread 1/4" - 2"
Flanged 1" - 8"
Body Material Brass, Stainless Steel
Working Pressure 0.1 - 16 Bar
Working Temperature 0°C - 180°C

SPECIAL-PURPOSE SOLENOID VALVE



2/2 WAY CORROSION RESISTANT SOLENOID VALVE

PTFE / CPVC / UPVC PISTON TYPE

Normally Closed or Normally Open Type
Connection Thread 3/8" - 2" and Flange DN15 - DN200
Body Material PTFE / CPVC / UPVC
Working Pressure 0.1 - 6 Bar
Working Temperature -5°C - 130°C

EXPLOSION-PROOF FLAMEPROOF SOLENOID VALVE



2/2 WAY EXPLOSION-PROOF FLAMEPROOF SOLENOID VALVE

Normally Closed or Normally Open Type
Connection Thread 3/8" - 2" and Flange DN15 - DN200
Body Material Brass, Cast Iron, Stainless Steel
Working Pressure 0 - 16 Bar
Working Temperature -5°C - 130°C